



Air Top Evo 3900 / 5500

Air Top Evo 3900/5500 with more power and new functions.

Webasto's Air Top Evo air heaters are the first choice when it comes to providing economic heating of driver's cabs and vehicle interiors. They provide a high level of comfort thanks to quiet continuous heating and fast warm-up times. In addition to temperature pre-selection (with thermostat or digital timer) five further operating modes are available together with the optional multi-comfort Air Top Evo MC heater control.

This allows individual requirements to be met for a range of different environments (e.g. to save battery power in remote areas if rapid warmth is required in very cold climates or in mountainous regions with low ambient air pressure). These functions can of course also be used in combination with our Thermo Call and Telestart remote control units.



Eco: Energy saving mode

Enables the interior to be warmed at an economical 70% of the maximum heat output – for protecting both the battery and the environment.



Standard: Comfort heating

The heater runs at its nominal power for heating the cab when outside temperatures are low.



Plus: Quick heating mode

The heater runs at maximum (110% of nominal) power and heats up to the selected temperature level in an even shorter time (limited heating time).



Ventilation

Provides fresh air and helps the air-conditioning system work faster and more effectively.



Altitude mode

Adjusts combustion conditions to enable use at altitudes from 1,200m up to 2,200m above sea level.

Product benefits:

- Provides a high degree of environmental comfort in the driver's cab
- Powerful, quiet and continuous heating
- Compact size – easy and quick installation
- Proven quality
- Easy to use
- Diagnosis capability



Air Top Evo 3900 / Air Top Evo 5500
The powerful and comfortable air heater.



Control panel for Air Top Evo 3900 and 5500.

Technical specifications:



	Air Top Evo 3900	Air Top Evo 5500
Heat output (kW)	Diesel 1.5 – 3.5 (3.9 Plus*) Petrol 1.8 – 3.5 (3.9 Plus*)	Diesel 1.5 – 5.0 (5.5 Plus*) Petrol 1.8 – 5.0 (5.5 Plus*)
Air volume (m³/h) (against 0.5 mbar)	max. 132	max. 200
Fuel consumption (l/h)	Diesel 0.19 – 0.44 (0.49 Plus*) Petrol 0.25 – 0.49 (0.55 Plus*)	Diesel 0.19 – 0.63 (0.69 Plus*) Petrol 0.25 – 0.70 (0.77 Plus*)
Nominal voltage (V)	Diesel 12 / 24 Petrol 12	Diesel 12 / 24 Petrol 12
Electrical power consumption (W)	15 – 36 (45 Plus*)	15 – 90 (116 Plus*)
Dimensions (L x W x H) (mm)	423 x 148 x 162	423 x 148 x 162
Weight (kg)	5.9	5.9

* Expanded heating power "Plus" possible with control panel Air Top Evo MC



	Air Top Evo MC 04/05
Nominal voltage (V)	12 / 24
Electrical power consumption max. (mA)	3
Electrical power consumption max. off-state (mA)	<1.3
Dimensions (L x W x H) (mm)	122.2 x 80.4 x 32.5 122.2 x 80.4 x 42.0 (with frame)
Weight (g)	113
Environmental temperature (°C)	-40 to +85
Registrations	CE, e1